Specifications



# Batten weatherproof LED, Clipsal, 6W, IP54, black

CLITPBH

## Main

Range	Clipsal
Product name	TPWP Series
Product or component type	Batten light
Device application	Lighting

## Complementary

Type of installation	Outdoor
[Ue] rated operational voltage	230240 V AC 50 Hz
Colour rendering index	R <sub>a</sub> =80
Luminous flux	600 lm
Bulb lifespan	50000 h
Colour temperature	3000 К 4000 К 5700 К
Mounting mode	Ceiling
Electrical insulation class	Class II
Light source	LED
Shape	Round
Height	196 mm
Width	196 mm
Depth	58 mm
Colour tint	Black

## Environment

IP degree of protection	IP57
IK degree of protection	IK08
Relative humidity	1095 %
Ambient air temperature for operation	-1045 °C
Targeted country	Australia

## **Packing Units**

Unit Type of Package 1

Number of Units in Package 1

PCE

1

19.5 cm
15 cm
19 cm
1.045 kg
CAR
4
21.3 cm
31.9 cm
39.9 cm
4.639 kg
PAL
144
102 cm
114 cm
114 cm
199 kg

Life Is On Schneider

## 🌔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

# Environmental footprint Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 104

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen content performance	Halogen free plastic parts product

### Use Again

### $\circlearrowright$ Repack and remanufacture

Circularity Profile

End of Life Information

## Product datasheet

Image of product / Alternate images

Alternative





## Product datasheet

**CLITPBH** 





