Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



LED Diffused Batten, Clipsal -Lighting, 18W, 600mm, 2250lm, white

CLITPDB600

Main

Range	Clipsal
Product name	TPDB Series
Product or component type	Batten light
Device application	Lighting
Market segment	Small commercial Residential

Complementary

Type of installation	Indoor/outdoor
Total system power	18 W
Light source	LED 18 W
[Ue] rated operational voltage	230/240 V AC 50 Hz
Luminous flux	2250 lm
Bulb lifespan	50000 h
Colour temperature	3000 K 4000 K 5000 K
Device mounting	Surface
Mounting mode	Surface mounting
IP degree of protection	IP20
IK degree of protection	IK02
Electrical insulation class	Class I
Length	600 mm
Width	70 mm
Height	68 mm
Shape	Rectangular
Net weight	930 g

Environment

Colour rendering index	R _a =80
Ambient air temperature for operation	-1045 °C
Relative humidity	1095 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	7.6 cm
Package 1 Length	63.3 cm
Package 1 Weight	1.091 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	18.5 cm
Package 2 Width	25.2 cm
Package 2 Length	71.5 cm
Package 2 Weight	7.211 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	150
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	194.275 kg

Contractual warranty

Warranty (in months)

200



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	328
Environmental Disclosure	Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen-free status	Halogen free product
PVC free	No
Silicone-free	No

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No

Product datasheet

CLITPDB600

Image of product / Alternate images

Alternative







CLITPDB600

