



Series connection time switch 24 hrs., segments, autonomy, 1 TLE

Part no. TSQD1NO
Catalog No. 167388
Alternate Catalog No. TSQD1NO
EL-Nummer (Norway) 0001456990

Design verification as per IEC/EN 61439

Technical data for design verification				
Rated operational current for specified heat dissipation	I_n	A		0
Heat dissipation per pole, current-dependent	P_{vid}	W		0
Equipment heat dissipation, current-dependent	P_{vid}	W		0
Static heat dissipation, non-current-dependent	P_{vs}	W		0.5
Heat dissipation capacity	P_{diss}	W		0
Operating ambient temperature min.		°C		-10
Operating ambient temperature max.		°C		50
				0

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Analogous time switch for distribution board (EC002304)				
Electric engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Analogous time switch (ec1@ss10.0.1-27-20-01-09 [ACN651011])				
Mounting method				DIN rail
Number of channels				1
Supply voltage		V		230 - 240
Voltage type of supply voltage				AC/DC
Frequency supply voltage		Hz		45 - 60
Autonomy in hours				72
Autonomy in years				0
Accuracy per day		s		1
60 min. program				No
24 h program				Yes
Weekly program				No
Annual program				No
Mains synchronous				No
Quartz controlled				Yes
Contact type				Normally open contact
Shortest switching time channel 1		min		15
Shortest switching time channel 2		min		0
Program shift divide 1		min		15
Program shift divide 2		min		0
Automatic switching summer-/winter time				No
Manual operation				Yes
Switching preselection				No
Nominal switching current at 250 V AC		A		16
Potential free switch contact				Yes
Degree of protection (IP)				IP20
Width in number of modular spacings				1
Width		mm		17.5
Height		mm		90
Depth		mm		65.5

