



VS212PT



Small distributor,golf,surface,2row,IP40,24M,MS-terminal,AUS,N+PE,white door

Technical characteristics

Architecture

Fixing mode surface-mounting

Functions

With a pipe-in lead Yes

Configuration

Number of modules 24

Main electrical features

Nominal voltage 400 V

Electric current

Rated current 80 A

Dimensions

Depth of installed product 99 mm

Internal depth 99 mm

Height of installed product 377 mm

Width of installed product 282 mm

Width in division units 12

Cover, door

Type of door closing Latch

Identification of protection index 40

Interlockable No

Number of keylock of the door 0

Cover type Closed (plain)

Door locking without

Door leave single

Cover type Door

Transparent cover or door No

Materials

Colour pure white

Colour white

RAL colour RAL 9010 - Pure white

Material plastic

Type of surface treatment untreated

Installation, mounting

Subject to technical modifications

Settings

| | |
|----------------|---------------------------|
| Enclosure type | Distributor empty cabinet |
|----------------|---------------------------|

Equipment

| | |
|--------------------------------------|-----|
| Number of rows | 2 |
| Quantity of section in width | 1 |
| Quantity of rails | 2 |
| Can be accessorized | Yes |
| Number of openings for flange plates | 0 |
| Extension possible | Yes |
| Earthing terminal block | Yes |
| Neutral terminal block | Yes |
| Signal passing door | Yes |

Standards

| | |
|-------------------------|-----------|
| GWT Glow wire test | 650 °C |
| European directive WEEE | concerned |

Safety

| | |
|---|---------------|
| IK protection code against mechanical impacts | IK07 |
| Protection index IP | IP40 |
| Protection class | isol.class II |
| Halogen free | Yes |
| Impact strength | IK07 |

Use conditions

| | |
|-----------------------|-------------|
| Operating temperature | -25...40 °C |
|-----------------------|-------------|