

Product data sheet Characteristics

WHB140-RG SWITCH 1 GANG 1P H/PROOF 250 V 40 A -Resistant grey





Main

- IVIGIII	
Range of product	Weathershield
Product brand	Clipsal
Device presentation	Basic element with complete housing

Complementary

Switch function	1-pole	
Number of poles	1	·
Device mounting	Surface	
Fixing mode	By screws	
Local signalling	without	
[Ue] rated operational voltage	250 V AC	
Rated current	40 A	
Marking	ON-OFF	
Marking location	Marking on surface	

Environment

Standards	AS 60529
	AS/NZS 60947-3
	IEC 60669-1
	AS/NZS 3947-3:approval number S/1

Packing Units

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.