



RIPPA 2 DOWNLIGHT TRI-COLOUR
206107N - 8W DOWNLIGHT WITH CCT AND SENSOR
 EGLO Lighting Australia
 Made in China


Thank you for purchasing a quality EGLO Ripa 2 downlight. Please read the following instructions carefully before installation. Keep this document for future reference.

WARNING!


Any electrical wiring must be carried out by a licensed electrician or qualified personnel. Installation must follow all relevant Australian wiring rules & standards.

INSTALLATION


Images are for reference only.




1 Turn power off at main electrical supply board.




2 Ensure that there are no cables or pipes in the ceiling cavity above where the downlight is to be installed. Using a 90 mm hole saw, carefully cut a hole in the plaster. Use appropriate eye protection, dust mask and appropriate safety apparatus to ensure adequate personal protection.




3 For model number 206107N (colour temperature selection switch on back of fitting), set the desired colour temperature (3000K, 4000K or 5000K) by toggling the switch on the back of the downlight BEFORE installation.




4 Insert the plug into the power socket located in the ceiling. Please note, if no power socket is present, one will need to be installed by a licenced electrician.



5 Fold the two side springs back against the downlight body simultaneously, whilst inserting into the pre-cut hole. Once inside the hole, the springs should naturally tense back down onto the top of the plaster ceiling to hold the downlight firmly in place.



6 This downlight has been tested and has achieved an IC-4 thermal rating, meaning it can be abutted and covered with thermal insulation in normal use. The minimum clearance distance from the luminaire to any normally flammable building element is 0mm. The minimum clearance distance from the top of the luminaire to any building insulation is 0mm.



7 Turn the power on at the mains supply board.

YOUR DOWNLIGHT/S ARE NOW READY FOR USE.



- 4 -