



Weatherproof Batten

TPWP Series

Technical brochure



Functionality and technology

Illuminate your space with our weatherproof batten!

The TPWP Weatherproof Batten is designed for versatility and durability, making it ideal for various applications such as warehouses, garages, residential homes and outdoor spaces. With models TPWP600 and TPWP1200, you can choose between power consumptions of 9 W/18 W and 18 W/36 W, respectively. Offering impressive lumen outputs of 1125 lm for the 9 W model and up to 4500 lm for the 36 W model, these battens ensure bright and efficient lighting. With an IP65 rating, they are built to withstand harsh conditions, making them perfect for general exterior applications.

Application

The TPWP battens are ideal for a variety of applications requiring reliable weatherproof lighting. Their robust design makes them suitable for outdoor areas such as walkways, garages, and industrial sites, as well as indoor environments that may be subject to moisture. With a high CRI of over 80, they ensure accurate colour rendering and improved visibility. Backed by a 5-year warranty, the TPWP series provides dependable performance, making it an excellent choice for both commercial and residential lighting needs.

Ordering matrix

Catalogue No.	Description
TPWP600	LED Weatherproof Batten, IP65, 600mm, colour changing and power shifting
TPWP1200	LED Weatherproof Batten, IP65, 1200mm, colour changing and power shifting

Tri-Temp
3000K/
4000K/
5700K

Power
Shift


5
Year
Warranty

clipsal.com


Life Is On

Schneider
Electric

TPWP Series

Specification		
Model	TPWP600	TPWP1200
Clip Material	Stainless steel clips	Stainless steel clips
Voltage	230/240 Vac, 50 Hz	
Power Consumption	9 W/ 18 W	18 W/ 36 W
Current	55 mA for 9 W	110 mA for 18 W
	110 mA for 18 W	220 mA for 36 W
Lumens	1125 lm for 9 W	2250 lm for 18 W
	2250 lm for 18 W	4500 lm for 36 W
CCT	3000/ 4000/ 5700K	
CRI	>80	
IP Rating	IP65	
LED Lamp Life (L70)	50,000 Hrs	
Storage/ Transportation Temperature	-10°C to 45°C	
Operation/ Storage/ Transportation Humidity	10% to 95% RH Non-condensing	
Compliance		
Warranty	5 Years	
Class	I	

Construction		
Model	TPWP600	TPWP1200
Length (L)	640 mm	1,240 mm
Width (W)	102 mm	102 mm
Height (H)	84.5 mm	84.5 mm
Weight	~1.08 kg	~1.83 kg



Clipsal by Schneider Electric

33-37 Port Wakefield Road,
Gepps Cross,
South Australia 5094
www.clipsal.com

Consumer Support Enquiries

Phone: 13 73 28 (13 SEAU)
Website: clipsal.com/contact-us

Life Is On

Schneider
Electric